SNOWSTORM PICTURE CARS LLC • PRODUCTION ASSET DOSSIER

2019 CFMOTO CFORCE 600 4X4 EPS

Mid-Heavy All-Terrain Utility • Tactical Escort / Tow-Tracking / Heavy Remote Camera Rig

VEHICLE IDENTIFICATION:	**2019 CFMOTO CFORCE 600**	**CHASSIS VIN:**	**LCELDUZ47K6001645**
FLEET CLASSIFICATION:	Mid-Heavy 4x4 All-Terrain Utility (ATV)	**LIVERY / FINISH:**	Titanium Grey / Royal Blue & Textured Black Composite
DISPLACEMENT / OUTPUT:	580cc EFI • 40 HP • 36 lb-ft Torque	**DRIVETRAIN & STEERING:**	Selectable 2WD/4WD w/ Diff Lock • Electronic Power Steering (EPS)
OPERATIONAL STATUS:	Turnkey / Fully Inspected / Camera-Ready	**PRIMARY PRODUCTION ROLES:**	Tactical Law Enforcement, Search & Rescue, Tracking Rig, Utility Tow

1. MECHANICAL SPECIFICATIONS & POWERTRAIN

SYSTEM	FACTORY SPECIFICATION	ON-SET & OPERATIONAL NOTES
Engine Architecture	580cc Single-Cylinder, 4-Stroke, 4-Valve, SOHC	Liquid-cooled; high low-end torque curve for steady process tracking and towing.
Fuel Delivery System	Bosch® Electronic Fuel Injection (EFI)	Smooth, predictable throttle response for low-speed camera movements and reset marks.
Transmission & Gearing	CVTech® Automatic (P / R / N / H / L) w/ Engine Braking System	Integrated downhill descent control prevents runaways on steep off-road location inclines.
Drive Select Mode	Push-Button 2WD / 4WD w/ Front Differential Lock	Instant electric actuation for mud, loose shale, forest floors, or sand.
Power Steering	Electronic Power Steering (EPS)	Variable assist reduces fatigue for precision drivers and provides smooth tracking lines.
Cooling & Capacity	Liquid-Cooled w/ High-Capacity Radiator • 4.75 Gal Tank	Extended continuous idling capacity during long camera and lighting setups without heat soak.

2. DIMENSIONS, CHASSIS & TRANSPORT LOGISTICS

METRIC	DIMENSION / RATING	TRANSPORT & CLEARANCE GUIDELINES
Overall Dimensions	89.0" L × 46.5" W × 48.0" H	Mid-chassis footprint; loads smoothly onto standard utility trailers, flatbeds, and truck beds.
Wheelbase & Ground Clearance	Wheelbase: 58.0" • Ground Clearance: 10.6"	Longer wheelbase delivers improved pitch stability during rapid acceleration and braking.
Curb Weight	870 lbs (395 kg)	Substantial weight provides stable, weighted camera tracking platform in rough terrain.
Suspension Architecture	Independent Double A-Arm (Front & Rear)	Adjustable preload shock absorbers tuned for minimal chassis roll during tracking shots.
Wheels & Tires	25" Heavy-Duty All-Terrain Tires on 12" Aluminum Alloy Rims	Aggressive directional tread pattern; dressed in optical matte tire dressing for camera readiness.
Braking Hardware	4-Wheel Hydraulic Disc Brakes	Progressive stopping control engineered for reliable cue resets and stunt rehearsals.

CAMERA RIGGING, TOWING & GRIP EQUIPMENT CAPABILITIES

- **Front Winch:** Factory installed 3,000 lb heavy-duty electric winch with roller fairlead (functional for recovery or tactical prop staging).
- **Hitch & Tow Rating:** Standard 2-inch automotive receiver rated for **1,000+ lbs towing capacity** (excellent for towing sound carts, lighting dollies, or camera chase rigs).
- **Composite Heavy-Duty Cargo Racks:** Integrated steel-reinforced composite racks • **Front: 100 lbs** • **Rear: 150 lbs** capacity. Provides vetted hardpoints for Matthews/Modern grip cheese plates, monitor cages, and remote cinema head setups.

ON-CAMERA ROLE CLASSIFICATIONS & PRODUCTION COMPLIANCE

• **On-Camera Hero Role:** Tactical police/border patrol unit, military compound perimeter vehicle, mountain rescue quad, or rugged utility security transport.
• **Behind-the-Scenes Production Rig:** Remote camera chase vehicle, grip/electric gear hauler in rugged backcountry locations, off-road dolly tug.
• **Insurance & Execution:** Deployed under **Form SPC-01** (Master Picture Vehicle Agreement) or **Form SPC-02** (Stunt Addendum) with mandatory $1,000,000 CGL coverage naming Snowstorm Picture Cars LLC as Additional Insured and Loss Payee.

Snowstorm Picture Cars LLC • Commercial Dispatch • Inquiries, reservations, and turnkey transport: **shelton@snowstormproperties.com**